

DECLARATION OF PERFORMANCE No. 06-20/30-CPR-2016

Description of product:

- Name, type: paving grade bitumen 20/30
- Standard: LST EN 12591:2009

Intended use: in the construction and maintenance of roads, airfields and other paved areas

Manufacturer: Public Company ORLEN Lietuva, Juodeikiai vill., LT-89467 Mažeikiai distr., Lithuania Place of manufacture: Public Company ORLEN Lietuva, Juodeikiai vill., LT-89467 Mažeikiai distr., Lithuania

System of Assessment and Verification of Constancy of Performance: +2

Information on notified body: Notified certification body No. 1567 – State Enterprise *Problematika*, Galves St. 2, LT-02241 Vilnius, Lithuania – performed the initial inspection of the factory and of factory production control and performs the continuous surveillance, assessment and approval of the factory production control, and, on 4 October 2010, issued the *Certificate of Factory Production Control No. 1567-CPD-0064*.

Declared performance

Essential characteristics	Performance	Harmonized Standard
Penetration at 25 °C	20–30 x 0,1 mm	LST EN 12591:2009
Softening point	55–63 °C	
Flash point	≥ 240 °C	
Solubility	≥ 99,0 %	
Penetration index	NR (no requirement)	
Kinematic viscosity at 135 °C	≥ 530 mm²/s	
Dynamic viscosity at 60 °C	≥ 440 Pa·s	
Fraass breaking point	NR (no requirement)	
Resistance to hardening at 163 °C:		7
retained penetration at 25 °C	≥ 53 %	-
increase in softening point	≤ 8 °C	
change of mass	≤ 0,5 %	

References: The actual performance of the product – paving bitumen produced according to the **Technical Requirements Specification** TRA BITUMAS 08/14 and **LST EN 12591:2009** – is in conformity with the hereby declared performance. This Declaration of Performance has been issued under the responsibility of the manufacturer Public Company ORLEN Lietuva.

Signed on behalf of the manufacturer

Deputy Director of Technology and Investment

(signatory job title)

Juodeikiai vill., Mažeikiai distr., Lithuania 2016-04-25

Piopos

Linas Čiapas (name, surname)